







List of IP Cameras

MODEL	ITEM	DESCRIPTION
	IPS-100	22x Mpeg-4 IP Speed Dome Camera <ul style="list-style-type: none"> ● Integrate VIDEO SERVER 22x high speed dome camera ● 1/4" High Resolution CCD sensor ● MPEG-4 Advanced Simple Profile, DVD resolution at lower data rates and smaller file sizes ● MPEG-4 D1 resolution 720 * 480 ● System On a Chip(SoC) ● QoS (802.1pQ) for high quality video stream(IP multicast, IGMP supported) ● Digital TimeCode Embedded ● Built-in LAN and WAN(PPPoE supported) ports, DDNS supported. ● Simultaneously analog and digital outputs ● Live video variation setting – Brightness/Contrast/Hue/Saturation ● Waterproof adaptor box included for AC220 to AC24v for outdoor
	IPS-200	27x Day & Night Mpeg-4 IP Speed Dome Camera <ul style="list-style-type: none"> ● 27x Day & Night camera module. <i>same spec as IPS-100</i>
	IVD-100	Mpeg-4 IP Video Decoder <ul style="list-style-type: none"> ● Built in LAN / WAN (Low latency PPPoE supported) digital video Decoder. ● MPEG-4 up to D1 resolution ● QoS enabled (L2, L3) video streaming ● Reset function for getting default configuration ● Digital Time embedded. ● DDNS supported.

MODEL	ITEM	DESCRIPTION
	SecuNET-150A	1 Ch Video / Audio MPEG-4 IP Video Server (by D1 compression) <ul style="list-style-type: none"> ● MPEG-4 D1 resolution 720x480 ● Built-in 2-way audio ● LAN and WAN 2 ports ● Including switching power adapter

MODEL	ITEM	DESCRIPTION
	CMI-100	MPEG4 IP Color Box Camera <ul style="list-style-type: none"> ● MPEG-4 D1 IP resolution 720x480 ● 1/3" Color Sony CCD, Resolution 380TVL, 0.5Lux/F1.2 ● Including switching power adapter
	CMI-H200	MPEG4 IP Color Hi-Resolution Box Camera <ul style="list-style-type: none"> ● MPEG-4 D1 IP resolution 720x480 ● 1/3" Color Sony CCD, Resolution 480TVL, 0.5Lux/F1.2 ● Including switching power adapter
	IPR-200	MPEG4 IP 40M IR Waterproof camera <ul style="list-style-type: none"> ● MPEG-4 D1 IP resolution 720x480, 1/3" Color Sony CCD, NTSC 537H*505V; PAL 537H*597V ● Resolution 380TVL, 0.2Lux/F1.2, 0Lux(IR ON), S/N: 48Db ● Auto Electronic Shutter, Board Lens F8.0mm (option : F6.0mm/12mm), AC100~240V W/FAN+HEATER, IP66. ● Including switching power adapter